

ELD500 PRECISION LEAK DETECTOR

edwardsvacuum.com

Edwards ELD500 fully automated leak detector has arrived. It's designed for fast, accurate leak detection in a wide range of applications and is fully mobile with an easy to use control interface. Edwards ELD500 is your perfect partner in leak detection.

- Low cost of ownership
- Customisable for any application
- Ready to go mobile solution
- High stability and accuracy



Technical data

| ELD500 Leak Detector | Units | WET | DRY | FLEX |
|--|--------------------------------|-------------------------|-------------------------|---------------------------|
| Lowest detectable helium leak rate | | | | |
| Vacuum operation | mbar ls ⁻¹ | ≤ 5 x 10 ⁻¹² | ≤ 3 x 10 ⁻¹¹ | ≤ 5 x 10 ⁻¹² * |
| Sniffer operation | mbar ls ⁻¹ | ≤ 7x10 ⁻⁹ | ≤ 7x10 ⁻⁹ | ≤ 7x10 ⁻⁹ |
| Maximum measurable helium leak rate | | | | |
| Vacuum operation | mbar ls ⁻¹ | > 0.1 | > 0.1 | > 0.1 |
| Measurement ranges | decades | 12 | 12 | 12 |
| Maximum permissible inlet pressure | mbar | 15 | 15 | 15 |
| Pumping speed during pumpdown, 50 Hz/60 Hz | m ³ h ⁻¹ | 2.5/3 | 1.6/1.8 | N/A |
| Helium pumping speed in the fine mode | ls ⁻¹ | 3.1 | 3.1 | 3.1 |
| Time constant for leak rate signal | s | < 1 | < 1 | < 1 |
| Time until ready for operation | min | ≤ 2 | ≤ 2 | ≤ 2 |
| Power consumption | VA | 420 | 350 | 200 |
| Inlet flange | | NW25 | NW25 | NW25 |
| Dimensions (WxHxD) | mm | 495x456x314 | 495x456x314 | 495x456x314 |
| Weight | kg | 40 | 35.5 | 30 |

* backing pump dependent

Ordering information

| Product Description | Order Number |
|--|--------------|
| ELD500 WET, 200-240V,50/60Hz | D13510903 |
| ELD500 WET, 100-120V, 50/60Hz | D13510904 |
| ELD500 WET, 100-120V, 60Hz | D13510906 |
| ELD500 DRY, 200-240V,50/60Hz | D13520903 |
| ELD500 DRY, 100-120V, 50/60Hz | D13520904 |
| ELD500 DRY, 100-120V, 60Hz | D13520906 |
| ELD500 FLEX, 100-240V,50/60Hz | D13530000 |
| ELD500 RC - Wired - Remote control | D13550100 |
| ELD500 RC - Wireless - Remote control | D13550110 |
| ELD500 RC - Wired - 8m extension cable | 14022 |
| ELD500 RC - Wireless - Extra transmitter | D13550130 |
| ELD500 SL - Standard sniffer line 4m | D13550300 |
| ELD500 SL - Extended SL Interface | D13550200 |
| ELD500 SL - Extended sniffer line 5m | 14008 |
| ELD500 SL - Extended sniffer line 20m | 14009 |

| Product Description | Order Number |
|---|--------------|
| ELD500 SL - Extended sniffer line 50m | 12183 |
| ELD500 Partial flow adaptor | D13550400 |
| ELD500 Transport Case | D13550500 |
| ELD500 Cart without Ebox | D13550600 |
| ELD500 SG - Helium spray gun | 16555 |
| CL-Internal calibrated leak | D13550910 |
| CL-Cal Leak bspk. 0.5 - 1E-7. Screw Skt | D13550930 |
| CL-calibrated leak HE 4 to 6 | D13550950 |

Extended warranty

| Product Description | Order Number |
|---|--------------|
| Extended warranty from 18 months to 3 yrs | EW3AA5100 |
| Extended warranty from 18 months to 5 yrs | EW5AA5100 |

GLOBAL CONTACTS

Publication Number: 3601 0358 01

© Edwards Limited 2018. All rights reserved Edwards and the Edwards logo are trademarks of Edwards Limited

Whilst we make every effort to ensure that we accurately describe our products and services, we give no guarantee as to the accuracy or completeness of any information provided in this datasheet.

Edwards Ltd, registered in England and Wales
No. 6124750, registered office: Innovation Drive,
Burgess Hill, West Sussex, RH15 9TW, UK.

EMEA

| | |
|---------|---|
| UK | +44 1444 253 000 (local rate) 08459 212223 |
| Belgium | +32 2 300 0730 |
| France | +33 1 4121 1256 |
| Germany | 0800 000 1456 |
| Italy | + 39 02 48 4471 |
| Israel | + 972 8 681 0633 |

ASIA PACIFIC

| | |
|-----------|------------------|
| China | +86 400 111 9618 |
| India | +91 20 4075 2222 |
| Japan | +81 47 458 8836 |
| Korea | +82 31 716 7070 |
| Singapore | +65 6546 8408 |
| Taiwan | +886 3758 1000 |

AMERICAS

| | |
|--------|------------------|
| USA | +1 800 848 9800 |
| Brazil | +55 11 3952 5000 |

